

Connecting Tubings



INTRODUCTION

The product is intended to connect pipelines and devices which provides pathway of the liquid-injection or/and invasive blood pressure monitoring in interventional operation.

PRODUCT FEATURES

- High pressure resistance: 500psi/1200psi
- Transparent material makes the flow visible
- Customized sizes are available

ORDERING INFORMATION

500 PSI female to male luer lock

External OD (mm)	Length (cm)						
	10	20	30	60	90	120	150
3.00	BM-CT3.00-10	BM-CT3.00-20	BM-CT3.00-30	BM-CT3.00-60	BM-CT3.00-90	BM-CT3.00-120	BM-CT3.00-150

BRAIDED TUBING

1200 PSI female luer lock to male rotator

External OD (mm)	Length (cm)						
	20	60	90	120	150	180	200
3.65	BM-CT3.65-20B	BM-CT3.65-60B	BM-CT3.65-90B	BM-CT3.65-120B	BM-CT3.65-150B	BM-CT3.65-180B	BM-CT3.65-200B

*CE not available for length of 180/200cm

NON-BRAIDED TUBING

1200 PSI female to male luer lock

External OD (mm)	Length (cm)						
	20	60	90	120	150	180	200
3.20	BM-CT3.20-20A	BM-CT3.20-60A	BM-CT3.20-90A	BM-CT3.20-120A	BM-CT3.20-150A	BM-CT3.20-180A	BM-CT3.20-200A

*CE not available for length of 180/200cm